

# WALL-MOUNTED DELUXE - R410A



## Features



### Energy Saving

Save more with the advance compressor and coil technology.



### Rapid Cooling

Achieve faster cooling with our true 5-speed fan design.



### Healthy Ionizer

Breathe fresher and healthier air for your family with the ion purifier.



### Quiet Mode

Experience peace and comfort at home with the use of the quiet mode.



### Air Surround

Feel the breeze with our 3D airflow technology that ensures even air circulation in your home.



### Elegant Design

Aesthetically designed with hidden temperature display on a classy high gloss surface.



## Other Features



Comfortable Sleep




Auto Mode



24 HourTimer



Intelligent Air




Auto Swing



Exquisite Filter



3 Minutes Protection



Auto Restart



Self - Diagnosis

## SPECIFICATIONS

### Indoor Unit



### Outdoor Unit



### Wireless Remote Controller



### Wired Remote Controller (Optional)



Indoor Unit	Wireless	YWM3F10DAS-W	YWM3F15DAS-W	YWM3F20DAS-W
Outdoor Unit		YSL3F10AAS	YSL3F15AAS	YSL3F20AAS
Cooling Capacity	Btu/hr	10,000	13,000	18,600
Input Power	W	899	1,170	1,895
Rated Current	A	3.91	5.09	8.24
EER	Btu/hr/W	11.12	11.11	9.82
CSPF	Wh/Wh	3.31	3.24	3.02
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz		
Refrigerant Type/ Control		R410A / OUTDOOR CAP.TUBE		
Indoor Air Flow (H/L)	CFM	325/200	445/275	585/400
Noise Level (H/L)	dB(A)	33/28	40/34	42/35
Dimension (WxHxD)	Indoor	mm	815x280x205	900x310x215
	Outdoor	mm	780x540x245	780x540x245
Unit Weight	Indoor	kg	10.50	12.00
	Outdoor	kg	27.50	35.00
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	6.35 / 1/4
	Gas	mm/in	9.52 / 3/8	12.70 / 1/2

Indoor Unit	Wireless	YWM3F25DAS-W	YWM3F30DAS-W
Outdoor Unit		YSL3F25AAS	YSL3F30AAS
Cooling Capacity	Btu/hr	24,000	28,000
Input Power	W	2,450	2,855
Rated Current	A	10.65	12.41
EER	Btu/hr/W	9.80	9.81
CSPF	Wh/Wh	3.07	3.00
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz	
Refrigerant Type/ Control		R410A / OUTDOOR CAP.TUBE	
Indoor Air Flow (H/L)	CFM	710/465	710/465
Noise Level (H/L)	dB(A)	43/38	44/39
Dimension (WxHxD)	Indoor	mm	1,115x336x248
	Outdoor	mm	810x688x288
Unit Weight	Indoor	kg	16.30
	Outdoor	kg	47.00
Refrigerant Piping	Liquid	mm/in	9.52 / 3/8
	Gas	mm/in	15.88 / 5/8

#### Note:

- All designs and specifications are subjected to change without prior notice for product improvement
- Nominal cooling capacity is based on the conditions below  
Power supply, 1Ph/230V/50Hz  
Cooling - Indoor: 27°C DB / 19°C WB and Outdoor 35°C DB / 24°C WB
- Units are tested and comply with the latest ISO5151



YORK-MY-WM3F410-1901

#### Head Office:

**Johnson Controls Hitachi Air Conditioning Sales Malaysia Sdn. Bhd. (1258224-H)**  
(Formerly known as Johnson Controls Air Conditioning Malaysia Sdn Bhd)

Luxor Tech. Centre, Level 2, No. 1A, Jalan Teknologi 3/4,  
Taman Sains Selangor 1, Kota Damansara PJU 5,  
47810, Petaling Jaya, Selangor Darul Ehsan,  
Malaysia.

#### Branches:

Penang Branch  
Tel. 04-397 0213 Fax: 04-397 2045

Johor Bahru Branch  
Tel. 07-354 9878 Fax: 07-354 9871

Kota Kinabalu Branch  
Tel. 088-448 350 Fax: 088-448 352

Kuching Branch  
Tel. 082-553 100 Fax: 082-553 200

**Customer Care Centre: 1800 - 88 - 9675**  
**Website: [www.york.com/my](http://www.york.com/my)**

Authorized Dealer